

## Beiblatt zum Sicherheitsdatenblatt / Supplement to the safety data sheet

### Abschnitt 1 / Section 1

#### 1.1 Produktidentifikation / Product identification

s. Original-Datenblatt / see original safety data sheet

#### 1.2 Verwendungen des Stoffs / Uses of the substance











s. Original-Datenblatt / see original safety data sheet

#### 1.3 Einzelheiten zum Lieferanten / Details of the supplier

Firmenname /	Supplier	Stürmer Maschinen GmbH,
Straße /	Street	Dr.-Robert-Pfleger-Str. 26,
Ort /	City	D-96103 Hallstadt
Tel. /	Phone	+49 (0)951 96555 - 0 (07:00 - 17:00 Uhr / 07:00 am - 05:00 pm)
E-Mail /	E-Mail	info@stuermer-maschinen.de

#### 1.4 Notrufnummer / Emergency Telephone

Wählen Sie die passende Notrufnummer anhand des GHS-Symbols auf Ihrem Gefahrgut oder entsprechend Abschnitt 2.2 des orig. Sicherheitsdatenblattes \*.  
Call the appropriate emergency number using the GHS symbol on your dangerous goods or according to section 2.2 of the original safety data sheet \*.

GHS Gefahren-piktogramm / GHS symbol	GHS-Kürzel/ GHS-no.	Mögliche Signalwörter/ Warning	Gefährdungsklassen / Description of hazards	Notrufnummer */ Emergency Phone *
	GHS01 bis GHS09			+49 (0)951 96555 - 590 Sammelnotrufnummer Gefahrstoffe
	GHS01	Gefahr oder Achtung / Danger or Attention	Explosive Stoffe/Gemische und Erzeugnisse mit Explosivstoff, selbstzersetzliche Stoffe/Gemische, organische Peroxide / Explosive substances / mixtures and products containing explosives, self-reactive substances / mixtures, organic peroxides	- 591
	GHS02	Gefahr oder Achtung / Danger or Attention	Selbstzersetzliche Stoffe/Gemische, organische Peroxide, entzündbare Gase, Aerosole Flüssigkeiten, Feststoffe, selbsterhitzungsfähige Gemische, pyrophore Flüssigkeiten und Feststoffe, Stoffe/Gemische, die bei Berührung mit Wasser entzündbare Gase bilden / Self-reactive substances / mixtures, organic peroxides, flammable gases, aerosols, liquids, solids, self-heating mixtures, pyrophoric liquids and solids, substances / mixtures which form flammable gases on contact with water	- 592
	GHS03	Gefahr oder Achtung / Danger or Attention	Oxidierende Gase, Flüssigkeiten, Feststoffe / Oxidizing gases, liquids, solids	- 593
	GHS04	Achtung / Attention	Verdichtete, verflüssigte, gelöste und tiefgekühlt verflüssigte Gase / Compressed, liquefied, dissolved and refrigerated liquefied gases	- 594
	GHS05	Gefahr oder Achtung / Danger or Attention	Verätzung der Haut, schwere Augenschäden, auch metallkorrosive Eigenschaften / Chemical burns to the skin, severe eye damage, also metal-corrosive properties	- 595
	GHS06	Gefahr / Danger	Äußerst schwere und schwere akute Gesundheitsschäden oder Tod / Extremely severe and severe acute damage to health or death	- 596
	GHS07	Achtung / Attention	Akute Gesundheitsschäden, Reizung der Haut, der Augen und der Atemwege, Sensibilisierung der Haut, narkotisierende Wirkungen / Acute damage to health, irritation of the skin, eyes and the respiratory tract, sensitization of the skin, narcotic effects	- 597
	GHS08	Gefahr oder Achtung / Danger or Attention	Chronische Gesundheitsschäden (Organschädigungen) bei einmaliger oder mehrmaliger Exposition, krebserzeugende, erbgutverändernde und fortpflanzungsgefährdende Wirkungen, Lungenschäden durch Eindringen von Substanzen in die Lunge (Aspirationsgefahr), Sensibilisierung der Atemwege / Chronic damage to health (damage to organs) after single or multiple exposure, carcinogenic, mutagenic and reproductive effects, lung damage due to the penetration of substances into the lungs (risk of aspiration), sensitization of the respiratory tract	- 598
	GHS09	Achtung oder ohne Signalwort/ Attention or without wording	Giftig für Wasserorganismen mit kurz- und langfristiger Wirkung / Toxic to aquatic organisms with short and long-term effects	- 599

\* 07:00 - 17:00 Uhr, außerhalb dieses Zeitraums kann die Nummer auf dem Sicherheitsdatenblatt angerufen werden / 07:00 am - 05:00 pm, outside this time, the number on the safety data sheet can be called

Für alle anderen Informationen siehe Original-Sicherheitsdatenblatt / For all other information, see the original safety data sheet

# MATERIAL SAFETY DATA SHEET

VALVE-REGULATED LEAD ACID BATTERIES  
MAINTENANCE-FREE NON-SPILLABLE



Series No: 9990920191120-001  
ACCORDING TO ISO 11014-2009 FORMAT

Version: 1.0

Date Issued: 20-Jan-2019

## SECTION 1- CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Sealed Lead Acid Battery, Valve Regulated Lead Acid Battery(VRLA BATTERY), GEL Battery, Motive Battery, EVF, DZM Series, TS Series, TF Series, TGS Series.

**Name of Company:**

ZHEJIANG CHANGXING TIANNENG POWER CO., LTD.

Address: No.18th, Baoqiao Road, Huaxi Industrial Zone of Changxing County, Zhejiang, China

Tel: +86-572-6058015

Fax: +86-572-6058015

E-mail: [export@tiannenggroup.com](mailto:export@tiannenggroup.com)

## SECTION 2- HAZARDA IDENTIFICATION

**Lead Oxides:** Under normal conditions of use, lead dust, vapors, and fumes are not generated. Hazardous exposure may occur when product is overheated, oxidized or otherwise processed or damaged to create dust, vapor or fumes.

**Inhalation:** Lead dust or fumes may cause irritation of upper respiratory tract or lungs.

**Skin Contact:** Lead Compounds are not readily absorbed through the skin.

**Eye Contact:** Lead Compounds may cause eye irritation.

## SECTION 3- COMPOSITION / INFORMATION ON INGREDIENTS

Substance/Mixture	Percent	CAS No.
Lead/Lead oxides	80-95%	7439-92-1
ABS Container	5%	9003-56-9
Antimony	1-5%	7440-36-0
Calcium	<0.5%	7440-70-2

# MATERIAL SAFETY DATA SHEET

VALVE-REGULATED LEAD ACID BATTERIES  
MAINTENANCE-FREE NON-SPILLABLE



## SECTION 4 - FIRST AID MEASURES

Emergency and First Aid Procedures: Contact with internal components if battery is opened/ broken.

Inhalation: Remove to fresh air. Give oxygen or artificial respiration if needed. Get immediate medical attention.

Eye Contact: Flush with plenty of water for at least 15 minutes, hold eyelids open. Get immediate medical attention.

Skin Contact: Remove contaminated clothing and flush affected areas with plenty of water for at least 15 minutes and obtain medical attention if necessary.

Ingestion: Do not induce vomiting. Dilute by giving large quantities of water. If available give several glasses of milk. Do not give anything by mouth to an unconscious person. Give CPR if breathing has stopped. Get immediate medical attention.

## SECTION 5 - FIRE FIGHTING MEASURES

**Flash Point:** Not Applicable

**Extinguishing Media:**

Use water, foam or dry powder, as appropriate to extinguish fire.

**Fire Fighting Procedures:**

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full-face piece operated in the pressure demand or other positive pressure mode. Fight fire from the maximum distance. Evacuate area.

**Specific Hazards:**

When involved in a fire, the battery may decompose and produce irritating fumes containing metal oxides. And plastic may create toxic vapors, gases or fumes during hot operation.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

**Personal Precautions:**

Wear appropriate personal protective equipment as specified in Section 8.

**Environmental Precautions:**

This material may be non-hazardous in ordinary use and may be discarded in accordance with applicable governmental regulations and take order with the demands of the environmental protection section.

# MATERIAL SAFETY DATA SHEET

VALVE-REGULATED LEAD ACID BATTERIES  
MAINTENANCE-FREE NON-SPILLABLE



## Methods of Clean up:

Spill and leaks are unlikely because cells are contained in a sealed case. In the event of a battery rupture, prevent skin contact and collect all released material in a plastic lined metal container. Prevent spill from entering drinking water supplies or streams. Any product recovery or disposal must comply with local, state, federal, international or country specific regulations.

## SECTION 7 - HANDLING AND STORAGE

**Handling:** It can be use normally under the temperature of -20~40 . All connections should be connected accurately to avoid the possibility of shorting connections. Do not let oil and water or other contaminations drop on the top of battery while working. Be sure to have logical discharge electricity and terminate voltage setting while working. Use only in the well-ventilated areas. Keep away from heat, sparks and open flames. Make available in the work area emergency shower and eyes wash. Avoid contact with skin and eyes. Use of full-length sleeves and pants; boots or work shoes are recommended for manufacturing operations.

**Storage:** Store in cool, dry, well-ventilated area and away from combustible materials, sources of ignition, excessive heat and direct sunlight. Do not store in sealed areas.

**Warning:** Not for use on children under 5 years old.

## SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Exposure Limit:

Lead, Lead Oxides (Chronic poison):

OSHA - PEL 0.05 mg/m<sup>3</sup>

ACGIH - TLV 0.05 mg/m<sup>3</sup>

NIOSH - REL < 0.10 mg/m<sup>3</sup>

### Respiratory Protection (Specify Type):

Provide general dilution ventilation to keep exposure to vapors as low as possible.

### Ventilation:

Local Exhaust: Good general ventilation should be used. Use local exhaust ventilation as needed so that exposure limits are met.

Mechanical (General): Provide general ventilation in possessing and storage areas so that exposure limits are met.

**Engineering Controls:** General room ventilation is sufficient during normal use and handling. Do not install these batteries in sealed, unventilated areas.

### Personal Protective Equipment (In the handling the battery):

**Hand Protection:** Rubber or neoprene gloves.

**Skin and Body Protection:** Wear acid resistant boots, apron or clothing. Use decontamination facilities (eye bath, safety shower, washing facilities).

# MATERIAL SAFETY DATA SHEET

## VALVE-REGULATED LEAD ACID BATTERIES MAINTENANCE-FREE NON-SPILLABLE



**Protective Gloves:** Rubber or neoprene gloves.

**Eye Protection:** Safety glasses with side shields and avoid eye contact.

**Other Protective Clothing or Equipment:** Protective clothing is required where repeated or prolonged skin contact may occur.

**Work/Hygienic Practices:** Remove jewelry, rings, watches and any other metallic objects while working on batteries. All tools should insulate to avoid the possibility of shorting connections. DO NOT lay tools on top of battery. Be sure to electricity from tools and individual person by touching a grounded surface in the vicinity of the batteries, but are heavy. Serious injury can result from improper lifting or installation. DO NOT lift, carry, install or remove pulling the terminal posts for safety reasons and because terminal posts and post seals may be damaged. DO KEEP a fire extinguisher and emergency communications the work area.

### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

**General Physical Form:** The battery is solid.

**Odor:** The battery is odorless.

**Solubility in Water:** Lead, lead oxide and lead sulfate are insoluble in water.

### SECTION 10 - STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions.

**Conditions to Avoid:** Direct sunlight, overheat, sparks and other sources of ignition.

**Incompatibility:** Incompatible with strong oxidizing agents, potassium, sodium.

**Hazardous Polymerization:** Hazardous polymerization will not occur.

### SECTION 11 - TOXICOLOGICAL INFORMATION

**Lead/Lead Oxides:** Toxic by ingestion or inhalation. Chronic poison.

Potential Chronic Health Effects:

Be slightly hazardous in case of skin contact (permeate).

CARCINOGENIC EFFECTS: Classified A3 (Proven for animal.) by ACGIH, 2B (Possible for human.) by IARC.

MUTAGENIC EFFECTS: Not available.

TERATOGENIC EFFECTS: Not available.

DEVELOPMENTAL TOXICITY: Not available.

The substance may be toxic to blood, kidneys, central nervous system (CNS).

Repeated or prolonged exposure to the substance can produce target organs damage.

# MATERIAL SAFETY DATA SHEET

VALVE-REGULATED LEAD ACID BATTERIES  
MAINTENANCE-FREE NON-SPILLABLE



## SECTION 12 - ECOLOGICAL INFORMATION

### Lead/Lead Oxides:

Eco-toxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation: Possibly hazardous short-term degradation products are not likely. However, long-term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are less toxic than the product itself.

Special Remarks on the Products of Biodegradation: Not available.

## SECTION 13 - DISPOSAL CONSIDERATIONS

### Waste Disposal Method:

Spent batteries must be treated as hazardous waste and disposed of according to local state, and federal regulations. A copy of this material safety data must be supplied to any scrap dealer or secondary smelter with battery. Put into dustbin, otherwise incineration, otherwise licensed landfill, or safe disposal as required by local, state, federal, international or country specific regulations.

### Empty Container Warnings:

Empty containers may contain product residue, follow MSDS and label warnings even after they have been emptied.

## SECTION 14 - TRANSPORT INFORMATION

### Identification and Proper Shipping Name:

Batteries, dry, electric storage.

**DOT (Department of Transportation):** Not regulated.

**UN Number:** Not regulated.

**Identification Number:** Not applicable.

**IMO:** Not regulated.

**IATA/ICAO Class:** Not regulated.

The regulations may change from time to time. Please consult the most recent version of the relevant regulations. Follow all regulations in your country.

## SECTION 15 - REGULATORY INFORMATION

### Lead/Lead Oxides:

EC# 231-100-4 CAS# 7439-92-1

NFPA Hazard Rating: Flammability = 0 Health = 1 Reactivity = 0

# MATERIAL SAFETY DATA SHEET

**VALVE-REGULATED LEAD ACID BATTERIES  
MAINTENANCE-FREE NON-SPILLABLE**



This chemical substance is not classified in the Annex I of Directive 67/548/EEC and not listed in a priority list (as foreseen under Council Regulation (EEC) No 793/93 on the evaluation and control of the risks of existing substances.).

## SECTION 16 - OTHER INFORMATION

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. RJS Standard Testing & Certification Center shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. License granted to make unlimited paper copies for internal use only.